

Cupcake 2 Edge AI Server

Up to 52 TOPS of AI Performance

Ruggedized Design

The Cupcake 2 combines the secure performance of a 4-Core Intel Atom SOC with up to a 52 TOPS AI Processing Board wrapped up in a compact, fan-less, rugged chassis. This allows the OS and Applications to run on the SOC while the TPU handles all the AI processing in parallel. This Edge AI Server is a capable performer for Delivery, Transportation, Retail, Agriculture, Healthcare, Manufacturing, Hospitality and Security.

Multiple Interfaces & Expansion Capabilities

The Cupcake 2 features an array of IO capabilities with 4 GbE POE ports, multiple USB, HDMI 2.0 and a selectable RS232. Internal and external expansion is available from an SD Card Slot as well as multiple M.2 slots for wireless communication, Micro SIM and an EDSFF Connector for the AI Processor.

SDK and ISV Software Available

Unigen is working with multiple IHVs and ISVs to provide access to the complete libraries for creating Neural Networks for custom applications. The SDK's can be utilized for internal programming for applications and ISVs are available to work with our platform to create end to end solutions.

Private Clouds

The Cupcake 2 platform has partners that are ready and able to provide direct to cloud solutions both on the premise as well as with local cloud colocation centers where data can be safely stored, made available for extra computation and accessed with excellent QoS for AI and management applications.

Options (See Selection Guide)

Available with WiFi, 4G, 5G, GPS, GSSS, Memory up to 32GB DDR4, Up to 7.68TB NVMe SSD



Unigen's Cupcake 2 Edge AI Server delivers a solid platform for Machine Learning and Inference AI in a compact and rugged enclosure. With the right combination of I/O Interfaces and Expansion Capabilities to capture and process video and multiple types of signals through its POE ports and then to deliver the processed data to the client either over a wired or wireless network. Supporting Neural Networks from the leading ISV providers, Cupcake 2 delivers the flexibility to allow custom solutions.

| System | |
|--|--|
| CPU | Intel® Atom® x6414RE Processor SoC |
| Memory | 16GB DDR4 2400 SO-DIMM |
| Graphics | Intel® UHD Graphics |
| Storage | 64GB SSD |
| Ethernet | GbE x 1, GbE With POE+ (30W Max) x 4 |
| Audio | Line in x1, Line out x 1, Mic in x 1 |
| Display | HDMI 2.0b x 1 |
| USB | USB 3.1 Type A x 2 USB Type C |
| Expansion Slot | SD card slot x 1 M.2 2230 E-key x 1 for AI of WiFi M.2 2242/2280 M-key x 1 (SATA III/PCIe Gen 3.0) M.2 2042 B-key x 1 E1.S 4-lane PCIe 3.0 x 1 (EDSFF) for AI or Storage Micro SIM slot x 1 |
| I/O Placements | |
| Power | 12V DC-IN connector and power button |
| Reset | Reset button |
| Debug port | USB to UART Micro B |
| COM | D-Sub 9-pin connector x 1 selectable RS232 |
| CAN | 4-Pin terminal block header |
| Power | 12V DC 10A |
| Security | TPM 2.0 |
| OS Support | Linux, Microsoft |
| Dimension | 170mm x 158mm x 49.5mm |
| Operating Temperature | 0°C ~ 50°C |
| Benchmark | |
| Passmark Tests (Non-AI Performance) | Score (Composite: 1227.8 Marks) |
| Storage Performance | 1692 Marks |
| Memory Performance | 1036 Marks |
| CPU Performance | 2181 Marks |
| Low End Graphics | 59.3 Marks |
| Cinebench | 739.3 |
| WinRAR I/O | 1714 KB/s |

